MATERIAL SAFETY DATA SHEET

RIGHT-JOINT ASPHALT EXPANSION JOINT No. ASPH-001.M



Manufacturer: RIGHT/POINTE COMPANY

Address:

234 Harvestore Drive DeKalb, IL 60115

Telephone

815/754-5700

Fax:

815/754-5702

H.M.I.S.

Health:

Flammability:

Reactivity:

Personal Protection:

Hazard Rating: 0=least, 1-slight, 2=moderate, 3=high, 4=extreme, *=chronic

SECTION 1: Ingredients and Hazards

0

Exposure Limits

Asphalt:

65

TLV:

5mg/m3(fumes)

Limestone:

15

TLV:

15mg/m³ (dust)

Note: Right-Joint Asphalt Expansion Joint is an "Article" as defined by OSHA 29 CFR Part 1910.

SECTION 2: Physical Data

Solubility in Water:

N/A

Specific Gravity:

Appearance and Odor:

Solid black panel.

SECTION 3: Fire and Explosion Data

Flash Point and Method:

None

Autoignition Temperature:

Variable 390° to 500°F

Variable

Flammability Limits in Air: Extinguishing Media:

Water, Foam, Carbon Dioxide There are no unusual hazards associated.

Unusual Fire/Explosion Hazards: Special Fire Fighting Procedure:

Comments:

Not regulated by the D.O.T.

SECTION 4: Health Hazard Information

Stability:

Stable

Hazardous Polymerization:

Hazardous Decomposition Products: Carbon Dioxide, Carbon Monoxide. Under fire condition, aside from the above, fumes, smoke

hydrogen sulfide, sulfur oxides, aldehydes, and other decomposition products.

Will not occur.